



Belgian IPA

A generous hops schedule and soft Belgian Candi Sugar combine to create this modern style ale. Brewer's Best® Belgian IPA includes that trademark spiciness familiar to Belgian Style Ales along with the piney, herbal and slight citrus flavors of an American IPA. The result is a complex flavor combination that adds depth and outstanding character to this unique style of ale.

IBUs: 45 - 48

OG: 1.052 - 1.056

FG: 1.011 - 1.014

ABV: 5.5% - 6.0%

Difficulty: Intermediate Color: Pale Amber

Contents

- Ingredients
 - Priming Sugar
 - Grain Bag(s)
 - Bottle Caps
 - Brewing Procedures
- Hops may vary due to availability

Glossary

OG Original Gravity	DME Dried Malt Extract
SG Specific Gravity	LME Liquid Malt Extract
FG Final Gravity	IBU International Bittering Units (Tinseth)
CO2 Carbon Dioxide	ABV Alcohol by Volume

Ingredients

FERMENTABLES

- 6.6 lb. Pilsen LME
- 1.0 lb. Soft Candi Sugar

SPECIALTY GRAINS

- 8 oz. Caramel 40L
- 4 oz. Flaked Wheat

HOPS

- .5 oz. Magnum
- 1 oz. Simcoe
- 2 Packs of 1 oz. Chinook

YEAST

- 1 Sachet

Recommended Procedures

NOTE: This recipe incorporates late malt additions to ensure the lightest color possible for this beer style. Refer to BREW DAY SCHEDULE.

BREW DAY (DATE ___ / ___ / ___)

1. READ

Read all of the recommended procedures before you begin.

2. SANITIZE

Thoroughly clean and sanitize ALL brewing equipment and utensils that will come in contact with any ingredients, wort or beer.

3. STEEP GRAINS

Pour 2.5 gallons of clean water into your brew pot and begin to heat¹. Pour crushed grains into grain bag and tie a loose knot at the top of the bag². When the water is within an appropriate steeping temperature (150° - 165°F) place the grain bag into the brew pot³. Steep grains for approximately 20 minutes. Remove grain bag and without squeezing, allow liquid to drain back into brew pot. Your water is now wort.

4. START BOIL

Bring your wort to a gentle, rolling boil. Add **ONLY one of the included 3.3 lb. LME** to the boiling wort⁴. Continuously stir the extract into the wort as it returns to a gentle, rolling boil⁵.

5. FOLLOW SCHEDULE⁶

As directed on the BREW DAY SCHEDULE (right), slowly sprinkle the hops into the boiling wort. Be careful not to let the wort boil over the pot. Using the provided BREW DAY SCHEDULE, note the time the hops were added to help keep your brew on schedule. The BREW DAY SCHEDULE will guide you through the remaining addition of ingredients. Continue the gentle, rolling boil until the boil is complete.



Recommended Brew Day Equipment

- 4 Gallon Brew Pot (or larger)
- 6.5 Gallon Fermenter
- Airlock
- Long Spoon or Paddle
- Hydrometer
- Thermometer
- No-Rinse Sanitizer
- Cleanser

Brew Tips

¹We suggest doing a 2.5 gallon boil at minimum. If you have the equipment to boil more than 2.5 gallons feel free to do so. There is no need to change the amount of any of the ingredients.

²The grains should not be compacted inside the bag. Grains should steep loosely allowing the hot water to soak into all of the grain evenly.

³Pay careful attention not to let your steeping water exceed 170°F which leeches tannins into the wort.

⁴Run canisters of LME under hot water to allow the extract to pour easier.

⁵Pay careful attention that the extract does not accumulate and caramelize on the bottom of your brew pot.

⁶When consumed, hops can cause malignant hyperthermia in dogs, sometimes with fatal results.

BREW DAY SCHEDULE

1. Add .5 oz. Magnum hops _____ : _____ (time)
2. Boil 35 minutes
3. Add 1 oz. Simcoe hops and Soft Candi Sugar and **remaining 3.3 LME** _____ : _____ (time)
4. Boil 25 minutes
5. Add one pack of 1 oz. Chinook hops _____ : _____ (time)
6. Terminate boil _____ : _____ (time)

Total Boil Time: 60 Minutes
Continue to Step #6

Recommended Procedures (continued)

6. COOL WORT & TRANSFER

Cool the wort down to approximately 70°F by placing the brew pot in a sink filled with ice water⁷. Pour or siphon wort into a sanitized fermenter. Avoid transferring the heavy sediment (trub) from the brew pot to the fermenter.

7. ADD WATER

Add enough clean water (approx. 64° - 72°F) to the fermenter to bring your wort to approximately 5 gallons. Thoroughly stir the water into the wort. Be careful not to add a volume of water that will cause the wort to fall outside of the OG range specified in the BREW STATS⁸. Once you are satisfied your wort is at the proper volume and within the OG range, record the OG in the ABV% CALCULATOR (right).

8. PITCH YEAST

Sprinkle the contents of the yeast sachet over top of the entire wort surface and stir well with sanitized spoon or paddle. Firmly secure the lid onto the fermenter. Fill your airlock halfway with water and gently twist the airlock into the grommated lid. Move fermenter to a dark, warm, temperature-stable area (approx. 64° - 72°F).

FERMENTATION

9. MONITOR & RECORD

The wort will begin to ferment within 24 hours and you will notice CO₂ releasing (bubbling) out of the airlock. Within 4 - 6 days the bubbling will slow down until you see no more CO₂ being released. When fermentation is complete (no bubbles for 48 hours) take a FG reading with a sanitized hydrometer and record it in your ABV% CALCULATOR⁹.

DRY HOPPING

10. ADD DRY HOPS

Add the other pack of 1 oz. Chinook hops after you rack the beer into your secondary fermenter¹⁰. After a few days the hops will fall to the bottom of the fermenter and the beer can be carefully siphoned off on bottling day. If you do not use a secondary fermenter then add the hops to your primary after fermentation has completed and leave for 5-7 days before bottling.

BOTTLING DAY (DATE ___ / ___ / ___)

11. READ

Read all of the recommended procedures before you begin.

12. SANITIZE

Thoroughly clean and sanitize ALL brewing equipment and utensils that will come in contact with any ingredients, wort or beer.

13. PREPARE PRIMING SUGAR

In a small saucepan dissolve priming sugar into 2 cups of boiling water for 5 minutes. Pour this mixture into a clean bottling bucket. Carefully siphon beer from the fermenter to a bottling bucket. Avoid transferring any sediment. Stir gently for about a minute.

14. BOTTLE

Using your siphon setup and bottling wand, fill the bottles¹¹ to within approximately one inch of the top of the bottle. Use a bottle capper to apply sanitized crown caps.

15. BOTTLE CONDITION

Move the bottles to a dark, warm, temperature-stable area (approx. 64° - 72°F). Over the next two weeks the bottles will naturally carbonate. Carbonation times vary depending on the temperature and beer style, so be patient if it takes a week or so longer.

**CHILL & ENJOY YOUR TASTY BREW AND THANK YOU FOR
CHOOSING BREWER'S BEST® PRODUCTS.**

Brew Tips

⁷To avoid bacteria growth do this as rapidly as possible. Do not add ice directly to the wort. Alternatively, you can use a brewing accessory like a Wort Chiller.

⁸Use a sanitized hydrometer while adding water to monitor the SG.

⁹Consider transferring your beer to a secondary carboy, see "Two-Stage (Secondary) Fermentation" sidebar below.

¹⁰Optionally, you can place the hops in a mesh bag attached to a string. This will allow you to easily remove the hops before siphoning the beer into your bottling bucket.

¹¹Use standard crown bottles, preferably amber color. Make sure bottles are thoroughly clean. Use a bottle brush if necessary to remove stubborn deposits. Bottles should be sanitized prior to filling.

Two-Stage (Secondary) Fermentation

Brewer's Best® recommends home brewers employ the practice of a two-stage fermentation. This will allow your finished beer to have more clarity and an overall better, purer flavor. All you need is a 5-gallon carboy, drilled stopper, airlock and siphon setup to transfer the beer. You will also need to monitor and record the SG with your hydrometer when the beer is in the 'primary'. When the fermentation slows (5-7 days), **but before it completes**, simply transfer the beer into the carboy and allow fermentation to finish in the 'secondary'. Leave the beer for about two weeks and then proceed to Bottling Day. Consult your local retailer to learn more about this technique.

(SECONDARY RACK DATE ___ / ___ / ___)

Recommended Bottling Day Equipment

- 6.5 Gallon Bottling Bucket
- Bottle Brush
- Siphon Setup
- Capper
- Bottle Filling Wand
- Sanitizer
- 12 oz. Bottles (approx. 53)
- Brewer's Best® Crown Caps

ABV% Calculator

(OG - FG) x 131.25 = ABV%

(_____ * - _____ **) x 131.25 = _____ %

*OG from Step #8

**FG from Step #10



Brewer's Best is a registered trademark of the LD Carlson Co.